



AHV15 High Voltage Resistor

Issue 1.0 June 2011

Units 1 - 2, Tanfield Lea South Industrial Estate,
Stanley, Co Durham DH9 9XA
Telephone : + 44 (0) 1207 230 728 Fax : + 44 (0) 1207 281 860
EMail : sales@tsec.ltd.uk WEB : www.tsec.ltd.uk

TSEC manufacture a range of standard high voltage resistors which cover a range of resistances over a selection of maximum operating voltages. Applications include snubber and high voltage resistors in power supply, medical and military products.

Summary

High reliability thick film technology.
Maximum voltage 10KV (epoxy)
Maximum power dissipation 2.3W (@70 C)
Radial and axial configurations.
Conformal epoxy coat available

Mechanical Layout

Axial and radial designs.
Overall dimensions 20mm x 13.7mm (max)
Refer to AHV Packages document for package detail.

Electrical Specification

	Min	Nom	Max
Typical resistor values (Ohms)	1K ±20% @100V		700M ±1% @100V
Maximum voltage	5kV free air		10kV epoxy
Maximum power dissipation			2.3W @ 70°C
TCR	±50ppm /°C		Optional
	±100ppm /°C		Optional
	±300ppm /°C		Standard
VCR	<2ppm / V *1		
Derating	Linearly from rated dissipation @70°C to zero @ 125°C		
Load stability	<0.5% 1000hrs @ rated power dissipation		
Operational temperature range	- 55°C		125°C

* 1 Application specific and may vary with how product is used

Custom resistor solutions are available upon request.

TSEC reserves the right to change specifications without the explicit need to notify customers.

Ordering Information

PREFIX	CONFIGURATION	RESISTANCE	TOLERANCE	TCR RANGE
AHV15	AE - Axial epoxy AS - Axial silicone RE - Radial epoxy RS - Radial silicone S - No wires silicone	X X X Nominal resistance Ohms KOHms Mohms	F $\pm 1\%$ G $\pm 2\%$ J $\pm 5\%$ K $\pm 10\%$ M $\pm 20\%$	O - Optional S - Standard